


Order Code: JT-200P-PFC

PRO TIG 200 PFC Pulse



The Jasic TIG 200 PFC Pulse operates on a wide input voltage range, 95-270V and is equipped with powerful IGBT components and a singular PCB for improved efficiency and maintenance.

This technologically advanced inverter is extremely user-friendly and offers reliable and consistent arc performance. The TIG 200 with high frequency starting also offers MMA functionality making it an ideal choice for maintenance or manufacturing.



Shoulder Strap
JSS-01



Trolley JIT-01



Optional



Site Bag JSB-01



Key Features

- DC Pulse TIG/MMA
- Single PCB construction, easy for testing and maintenance
- PFC energy saving technology
- IGBT Inverter technology
- High frequency inverter, high efficiency
- Digital Control, HF Arc Ignition 2T/4T
- Pulse frequency 0.5 - 200 Hz
- Easy start, stable and reliable arc
- Auto-compensation for voltage fluctuation
- Compact size, lightweight and modern design
- Heavy duty 35-50mm dinse sockets
- High quality tactile rubber finish to mouldings and handle
- Supplied in full colour packaging
- Generator friendly**



Technical Data



AC 95-270V - 50/60 Hz



TIG: 10 - 160
MMA: 10 - 125



TIG: 10 - 200
MMA: 10 - 180



65



Power Factor 0.99



Dimensions LxWxH
420 x 135 x 277



115V: 27.7A
230V: 14.2A



115V: 4
230V: 6



115V: 160A @ 60%
230V: 200A @ 30%



115V: 125A @ 60%
230V: 180A @ 25%



Class: IP21S/F



7.5

Package Includes

Inverter power source, TIG torch & adaptor, Gas regulator,
Work return lead and clamp, Operating instructions,
5 year warranty*

* 5 year warranty subject to product registration ** Generator should have regulated output