

SuitCase™ 8RC and 12RC

Issued March 2003 • Index No. M/6.5

Wire Feeder with Remote Control



Quick Specs

Industrial Applications

Shipbuilding
Construction
Heavy Manufacturing
Rental

Processes

MIG (GMAW)
Flux Cored (FCAW)

Input Power 24 VAC, 7 A/10 A

Weight 8RC: 22.0 lb (9.9 kg)
12RC: 25.5 lb (11.6 kg)

The Power of Blue.®



Remote voltage control — standard.

Standard gas solenoid controlling gas flow.

Totally enclosed, impact-resistant, flame-retardant case provides strength and durability, protecting components and weld wire from moisture, dust and contaminants.

Component assembly is easily removed for servicing.

Quick-change drive rolls are easy to change — no tools required.



Drive roll accessibility makes it easy to install wire, adjust tension and change drive rolls.

Versatile feeders can run wire diameters up to 5/64 in (2.0 mm).

Gas purge purges gas line without feeding wire, or energizing weld wire with OCV.

Thermal overload protection protects motor and control circuit against possible damage due to overloading conditions, or loose cable connections.

Digital meter option available for wirefeed speed or voltage display.

Specifications (Subject to change without notice.)



(Use with CC/CV, DC Power Sources.)

Model	Input Power	Welding Power Source Type	Input Welding Circuit Rating	Electrode Wire Diameter Capacity	Maximum Spool Size Capacity	Wire Speed	Dimensions	Net Weight
8RC	24 VAC, 7 A, 50/60 Hz	Constant Voltage (CV)	500 A at 100% Duty Cycle	Solid Wire: .023–5/64 in (0.6–2.0 mm) Flux Cored: .030–5/64 in (0.8–2.0 mm)	8 in (203 mm) 14 lb (6.4 kg)	75–700 IPM (1.9–17.7 m/min)	H: 14-1/2 in (368 mm) W: 6-1/2 in (165 mm) D: 15-5/8 in (397 mm)	22 lb (9.9 kg)
12RC	24 VAC, 10 A, 50/60 Hz			Solid Wire: .023–5/64 in (0.6–2.0 mm) Flux Cored: .030–5/64 in (0.8–2.0 mm)	12 in (305 mm) Up to 44 lb (20 kg)		H: 16 in (406 mm) W: 7-1/4 in (184 mm) D: 20 in (508 mm)	25.5 lb (11.6 kg)



Wire feeder is warranted for 3 years, parts and labor.

MADE IN USA
APPLETON, WI



Welding Company NV
Brandekensweg 6
B-2627 Schelle
Belgium

TEL: +32.3 880 81 80
FAX: +32.3 880 81 99
info@weldingcompany.be

Web Site
www.weldingcompany.be





Drive Roll Kits (1 kit required, order from Miller Service Parts.)

Select drive roll kits from chart below according to type and wire size being used. Drive roll kits include 2 drive rolls, the necessary guides and feature an anti-wear sleeve for inlet guide.

Wire size	"V" groove for hard wire	"U" groove for soft wire or soft-shelled cored wires	"V" knurled for hard-shelled cored wires	"U" cogged for extremely soft wire or soft-shelled cored wires (i.e., hard facing types)
.023/.025 in (0.6 mm)	#087 131	—	—	—
.030 in (0.8 mm)	#079 594	—	—	—
.035 in (0.9 mm)	#079 595	#044 749	#079 606	—
.040 in (1.0 mm)	#161 189	—	—	—
.045 in (1.1/1.2 mm)	#079 596	#079 599	#079 607	#083 318
.052 in (1.3/1.4 mm)	#079 597	#079 600	#079 608	#083 317
1/16 in (1.6 mm)	#079 598	#079 601	#079 609	#079 614
.068/.072 in (1.8 mm)	—	—	#089 984	—
5/64 in (2.0 mm)	—	#079 602	#079 610	#079 615

Control Panels



1. Purge Switch
2. Voltage Control
3. Power Control Switch
4. Wire Speed Control

Ordering Information

Power Source and Options	Stock No.	Description	Qty.	Price
SuitCase™ 8RC (Remote Extension Cord required.)	#194 938	With remote voltage		
	#194 938-01-1	With meters, remote voltage, and trigger hold		
	#194 938-03-1	With CE, meters, remote voltage, and trigger hold		
Meter Kit	#195 165	Field. For SuitCase 8RC		
SuitCase™ 12RC (Remote Extension Cord required.)	#194 940	With remote voltage		
	#194 940-01-1	With meters, remote voltage, and trigger hold		
	#194 940-03-1	With CE, meters, remote voltage, and trigger hold		
Meter Kit	#195 169	Field. For SuitCase 12RC		
Accessories				
Remote Extension Cords (One required.)	#122 973	25 ft (7.6 m)		
	#122 974	50 ft (15.2 m)		
	#122 975	75 ft (22.9 m)		
Volt/Current Sensor Kit	#195 194	Field. For both SuitCase 8RC and 12RC. Required for digital meter operation with power sources not having pins F and H in the 14-pin receptacle. (PipePro 304 is the only Miller engine drive with pins F and H.)		
Flowmeter Kit	#195 217	Field. For both SuitCase 8RC and 12RC		
Shielding Gas Filter	#195 189	Field. For both SuitCase 8RC and 12RC		
Guns				
Ironmate™ 1260		Flux cored (FCAW) gun. See Lit. Index No. AY/16.0		
Roughneck® C-Series		MIG (GMAW) gun. See Lit. Index No. AY/17.0		
Power Sources				
XMT® 304		See Lit. Index No. DC/18.8		
Dimension™		See Lit. Index No. DC/19.2		
Invision™ MP		See Lit. Index No. DC/23		
Mark VI™		See Lit. Index No. DC/9.8		
Big Blue® 600D		See Lit. Index No. DC/10.3		
Big Blue® 402		See Lit. Index No. DC/10.8		
Big Blue® Air Pak™		See Lit. Index No. DC/10.5		
PipePro™		See Lit. Index No. ED/10.6		
Trailblazer®		See Lit. Index No. DC/4.5		
Consumables				
Drive Rolls/Wire				

Date:

Total Quoted Price:

Distributed by:

