



Super-silenced

Kubota water-cooled diesel, 1500rpm

EUROPOWER Generators

Europower super-silenced generating sets from 7,5 to 44kVA with Kubota water-cooled diesel engines, 1500rpm, 50Hz, 4 stroke

7,5 - 44kVA



EPS44TDE



Europower super-silenced generating sets from 7,5 to 44kVA with Kubota water-cooled diesel engines, 1500rpm, 50Hz, 4 stroke

Article code	TYPE	Alternator	kVA max.	kVA cont.	Amp. (cos phi 1)		Engine Kubota (EU Stage)	Cil.	kW	cm ³	Tank (l)	Cons. @75% load (l/h)	Autonomy @75% load (h)	Version (p.46)	Dimensions (cm)	kg	dB(A) @ 7m	LWA
					1 ~ 230V	3 ~ 400V												
951110911	EPS8DE	Sincro	7.5	7	30	-	D1105	3	8.4	1123	63	1.9	33.2	A8-AVR-ES-FG-FI4-LE-ODP-Y	150x64x90	430	60	85
991110913	EPS9TDE	Mecc Alte	9	8.5	12.2	12.3	D1105	3	8.4	1123	63	1.9	33.2	B9-AVR-ES-FG-FI4-LE-ODP-Y	150x64x90	440	60	85
951111111	EPS11DE	Sincro	11	10	43	-	D1703M	3	12.8	1647	73	2.6	28.1	A6-AVR-Erpm-ES-FG-FI4-LE-ODP-OL-Y	170x74x100	575	60	85
981111413	EPS14TDE	Leroy Somer	14	13	19	19	D1703M	3	12.8	1647	73	2.6	28.1	B11-AVR-Erpm-ES-FG-FI4-LE-LS2-ODP-OL-Y	170x74x100	580	60	85
991111413	EPS14TDE	Mecc Alte	14	13	19	19	D1703M	3	12.8	1647	73	2.6	28.1	B11-AVR-Erpm-ES-FG-FI4-LE-ODP-OL-Y	170x74x100	580	60	85
951111811	EPS18DE	Sincro	18	16	70	-	V2203M (IIIA)	4	17.2	2197	80	3.7	21.6	A6-AVR-Erpm-ES-FG-FI4-LE-ODP-OL-Y	198x74x100	700	62	87
981112013	EPS20TDE	Leroy Somer	20	19	29	27	V2203M (IIIA)	4	17.2	2197	80	3.7	21.6	B5-AVR-Erpm-ES-FG-FI4-LE-LS2-ODP-OL-Y	198x74x100	660	62	87
991112013	EPS20TDE	Mecc Alte	20	19	29	27	V2203M (IIIA)	4	17.2	2197	80	3.7	21.6	B5-AVR-Erpm-ES-FG-FI4-LE-ODP-OL-Y	198x74x100	660	62	87
991113011	EPS30DE	Mecc Alte	30	28	122	-	V3800DIT (IIIA)	4	38	3769	90	7.7	11.7	A10-Amp1-AVR-DSE-Erpm-ES-FG-FIA-Hz-LE-ODP-OL-PAI-WS-Y	210x94x112	970	65	90
981113413	EPS34TDE	Leroy Somer	33	30	43	43	V3300 (IIIA)	4	25	3318	90	6	15.0	B14-Amp3-AREP-AVR-DSE-ES-FG-FI4-Hz-LE-LS2-ODP-OL-WS-Y	210x94x112	870	65	90
991113413	EPS34TDE	Mecc Alte	33	30	43	43	V3300 (IIIA)	4	25	3318	90	6	15.0	B14-Amp3-AVR-DSE-ES-FG-FI4-Hz-LE-ODP-OL-WS-Y	210x94x112	900	65	90
981114413	EPS44TDE	Leroy Somer	44	40	61	58	V3800DIT (IIIA)	4	38	3769	90	7.7	11.7	B14-Amp3-AREP-AVR-DSE-Erpm-ES-FG-FI4-Hz-LE-LS2-ODP-OL-PAI-WS-Y	210x94x112	925	65	90
991114413	EPS44TDE	Mecc Alte	44	40	61	58	V3800DIT (IIIA)	4	38	3769	90	7.7	11.7	B14-Amp3-AVR-DSE-Erpm-ES-FG-FI4-Hz-LE-ODP-OL-PAI-WS-Y	210x94x112	970	65	90

Features & Benefits

Long Life



Kubota engines have a **high reputation** and long history for out of the box and in field quality and **durability**. Original Kubota matching tests are conducted for all Euro-power generating sets, which lead to a **unique worldwide service**.

Low noise



The **Kubota range** of Europower generating sets can indeed be called **"super-silenced"**. **Sound levels** vary from **60 to 65dB(A) at 7m** or from **85 to 90Lwa**. This is comparable with people speaking in a room or with an ordinary vacuum cleaner.

Trailer



Adapted trailers are available for each model (single axle, twin-axle, braked or unbraked version).

A.S.S.S.



A.S.S.S. or Automatic Start Stop System in case of mains failure. All these generators can be equipped with this **easy backup system**, which has a **built-in battery charger** and **computerized self-test**. When the mains fails, your generating set is up and running in minutes.

Regulated power



AVR stands for Automatic Voltage Regulator to maintain a **constant and stable voltage**. This results in better performance for sensitive appliances.

Preheating



Several **preheating devices** are offered as an option, such as cooling water preheating, oil pan preheating, air-intake preheating. These options / accessories allow the user to **start the engine in extremely cold conditions**.